





# SPECIFICATIONS - AVANT 750

 <b>LIFT CAPACITY</b> <b>1400</b> <b>kg</b>	 <b>ENGINE POWER</b> <b>49</b> <b>hp diesel</b>	 <b>LIFT HEIGHT</b> <b>3,0</b> <b>m</b>	 <b>SPEED</b> <b>25</b> <b>km/h</b>
---	---	---	---

## SPECIFICATIONS

Length	3060 mm
Width	see table
Height	2100 mm
Weight	1910kg
Standard wheels	320/55-15" TR/grass
Transmission, drive	hydrostatic
Aux. hydraulics oil flow / pressure	70 l/min 240 bar
Turning radius inside/outside	1240 / 2780 mm
Max. lifting height	3080 mm
Max. lifting capacity (hydr.)	2100 kg
Tipping load *	1400 kg
Max. breakout force / 50 cm	1700 kg
Engine make and type	Kubota V2403
Engine output (ISO Gross)	36 kW (49 hp)
Fuel	Diesel

\*) Load is measured at 400 mm from the attachment coupling plate, including attachment weight (70 kg) and with counterweights.

## DIMENSIONS



## PULLING FORCE

Wheel size	Drive speed	Pulling force
320/60-12 HD	22 km/h	1880 kp
320/55-15 HD	25 km/h	1600 kp

## WIDTH

Wheel size	745/750
27 x 8.50 - 15	1080 mm
26 x 12.00 - 12	1350 mm
320/60-12 HD	1350 mm
320/55-15 HD	1360 mm

## HEIGHT WITH CAB

	26x12.00-12 or...	320/55-15 wheels
LX Cab	2078 mm	2112 mm
DLX Cab	2105 mm	2139 mm
DLX with A/C on t...	2241 mm	2275 mm

