





# SPECIFICATIONS - AVANT 640

 <b>LIFT CAPACITY</b> <b>1100</b> <b>kg</b>	 <b>ENGINE POWER</b> <b>37,5</b> <b>hp diesel</b>	 <b>LIFT HEIGHT</b> <b>2,8</b> <b>m</b>	 <b>SPEED</b> <b>22</b> <b>km/h</b>
---	---	---	---

## SPECIFICATIONS

Length	2550 mm
Width	see table
Height	2035 mm
Weight	1420 + 170 kg
Standard wheels	26x12.00-12" Grass/TR
Transmission, drive	hydrostatic
Pulling force	1400 kp
Drive speed	11/22 km/h (2 speed)
Aux. hydraulics oil flow / pressure	66 l/min 200 bar
Turning radius inside/outside	900 / 2190 mm
Max. lifting height	2835 mm
Tipping load *	1000 kg
Max. breakout force / 50 cm	1250 kg
Engine make and type	Kubota V1505
Engine output (ISO Gross)	28 kW (37,5 hp)
Fuel	Diesel

## WIDTH

Wheel size	Width
27 x 8.50 - 15	1005 mm
23 x 10.50 - 12	1140 mm
26 x 12.00 - 12	1290 mm
320/60 - 12	1290 mm

## HEIGHT WITH CAB

Wheel size	23 x 10.50 - 12	26" wheels & 320/60-12	27 x 8.50 - 15
L Cab	2020 mm	2035 mm	2048 mm
LX Cab	2010 mm	2025 mm	2038 mm
DLX Cab	2030 mm	2045 mm	2058 mm
DLX with A/C on the roof	2166 mm	2181 mm	2194 mm

\*) Load is measured at 400 mm from the attachment coupling plate, including attachment weight (70 kg) and with counterweights.

## DIMENSIONS

