



# SPECIFICATIONS - AVANT 528



**LIFT CAPACITY**

**950**


**kg**



**ENGINE POWER**

**26**


**hp diesel**



**LIFT HEIGHT**

**2,8**

**m**



**SPEED**

**10**

**km/h**

## SPECIFICATIONS

Length	2550 mm
Width	see table
Height	1980 mm
Weight	1250 + 170 kg
Standard wheels	23x10.50-12" grass/TR
Transmission, drive	hydrostatic
Pulling force	950 kp
Drive speed max.	10 km/h
Aux. hydraulics oil flow / pressure	36 l/min 200 bar
Turning radius inside/outside	995 / 2050 mm
Max. lifting height (with telescop...)	2790 mm
Tipping load *	950 kg
Max. breakout force / 50 cm	1250 kg
Engine make and type	Kubota D1105
Engine output (ISO Gross)	19 kW (26 hp)
Fuel	Diesel

## WIDTH

Wheel size	Profile	Machine width
27 x 8.50 - 15*	TR tyre	1005 mm
23 x 8.50 - 12	TR / grass tyre	1090 mm
23 x 10.50 - 12	TR / grass tyre	1140 mm
26 x 12.00 - 12*	TR / grass tyre	1290 mm

\*) Bigger wheels will increase total machine height by 20-35 mm

## HEIGHT WITH CAB

Wheels	L Cab	LX Cab	DLX Cab
23" wheels	2020 mm	2010 mm	2030 mm
26" wheels & 320/60-12	2035 mm	2025 mm	2045 mm
27" wheels	2048 mm	2038 mm	2058 mm

\*) Load is measured at 400 mm from the attachment coupling plate, including attachment weight (70 kg).

## DIMENSIONS

